SAFETY DATA SHEET

1. Identification

Product identifier KAST-O-LITE 22 G PLUS; KAST-O-LITE 22 G PLUS WF

Other means of identification

Brand Code 5152, 909

For Industrial Use Only Recommended use

Avoid dry cutting, blasting, or dust generation. Users should be informed of the potential presence Recommended restrictions

> of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under

applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

HarbisonWalker International Company name

Address 1305 Cherrington Parkway, Suite 100

> Moon Township Pennsylvania

15108 US

Telephone General Phone: 412-375-6600

Website www.thinkHWI.com Not available. **Emergency phone number** Not available. Supplier

2. Hazard identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

> Specific target organ toxicity, repeated Category 1

exposure

Environmental hazards Not classified.

Label elements



Signal word

May cause cancer. Causes damage to organs through prolonged or repeated exposure. **Hazard statement**

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective

clothing/eye protection/face protection.

IF exposed or concerned: Get medical advice/attention. Response

Storage Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Other hazards None known.

Supplemental information Users should be informed of the potential presence of respirable dust and respirable crystalline

silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and

handling of this material should be provided as required under applicable regulations.

Material name: KAST-O-LITE 22 G PLUS; KAST-O-LITE 22 G PLUS WF

SDS CANADA 5152, 909 Version #: 01 Issue date: 05-18-2021

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Cement, Alumina, Chemicals		65997-16-2	40 - 60
Mullite		1302-93-8	20 - 40
Expanded Perlite		93763-70-3	2.5 - 10
SILICA, AMORPHOUS, FUMED	Fumed Silica Silica, crystalline free	7631-86-9	2.5 - 10
SILICA, CRYSTALLINE, CRISTOBALITE		14464-46-1	2.5 - 10
Titanium Dioxide		13463-67-7	0.1 - 2.5
Other components below reportable levels			10 - 25

Crystalline silica may be present at low concentrations; most of this is encapsulated in the coarse aggregate or as part of the clays or sands.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Symptoms may be delayed.

(show the label where possible).

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Prolonged exposure may cause chronic effects.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

medical attention and special treatment needed

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from

the chemical

Special protective equipment and precautions for firefighters

Use fire-extinguishing media appropriate for surrounding materials.

Not available.

Not applicable.

Not available.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

Material name: KAST-O-LITE 22 G PLUS; KAST-O-LITE 22 G PLUS WF 5152, 909 Version #: 01 Issue date: 05-18-2021

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Value Components	es Type	Value	Form
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Alberta OELs (Occupation Components	onal Health & Safety Code, Sc Type	hedule 1, Table 2) Value	Form
Expanded Perlite (CAS 93763-70-3)	TWA	3 mg/m3	Respirable particles.
,		10 mg/m3	Total particulate.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable particles.
		0.025 mg/m3	Respirable.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. British Columbia OELs. Safety Regulation 296/97, as ame		s for Chemical Substances, Oc	cupational Health and
Components	Туре	Value	Form
Expanded Perlite (CAS 93763-70-3)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable.
SILICA, AMORPHOUS, FUMED (CAS 7631-86-9)	TWA	4 mg/m3	Total
		1.5 mg/m3	Respirable.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.
,		10 mg/m3	Total dust.
Canada. Manitoba OELs (Reg. 21 Components	7/2006, The Workplace Safety Type	And Health Act) Value	Form
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Canada. Ontario OELs. (Control o	of Exposure to Biological or C Type	hemical Agents) Value	Form
Expanded Perlite (CAS 93763-70-3)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable fraction.

Material name: KAST-O-LITE 22 G PLUS; KAST-O-LITE 22 G PLUS WF 5152, 909 Version #: 01 Issue date: 05-18-2021

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)				
Components	Туре	Value	Form	
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3		

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)			
Components	Туре	Value	Form
Expanded Perlite (CAS 93763-70-3)	TWA	10 mg/m3	Total dust.
SILICA, AMORPHOUS, FUMED (CAS 7631-86-9)	TWA	6 mg/m3	Respirable dust.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Total dust.

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21)

Components	Туре	Value	Form
Expanded Perlite (CAS 93763-70-3)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	
Mullite (CAS 1302-93-8)	15 minute	20 mg/m3	Dust.
	8 hour	10 mg/m3	Dust.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	15 minute	10 mg/m3	Inhalable fraction.
	8 hour	0.05 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelinesOccupational exposure to nuisance dust (total and respirable) and respirable crystalline silica

should be monitored and controlled.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Use of an impervious apron is recommended.

Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels

exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.







General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Solid.

Not available. Color Odor Not available. **Odor threshold** Not available. Not available. Melting point/freezing point Not available. Not available. Initial boiling point and boiling

range

Not available. Flash point **Evaporation rate** Not available. Not available. Flammability (solid, gas) Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Not available. Explosive limit - upper (%) Not available. Vapor pressure Not available. Vapor density Not available. Relative density

Solubility(ies)

Not available. Solubility (water) Not available. **Partition coefficient**

(n-octanol/water)

Auto-ignition temperature Not available. Not available. **Decomposition temperature** Not available. **Viscosity**

Other information

Not explosive. **Explosive properties** Not oxidizing. Oxidizing properties

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Chlorine. Fluorine.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. **Serious eye damage/eye** Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

SILICA, CRYSTALLINE, CRISTOBALITE (CAS Irritant

14464-46-1)

Titanium Dioxide (CAS 13463-67-7) Irritant

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica

inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and

respirable crystalline silica should be monitored and controlled.

ACGIH Carcinogens

Mullite (CAS 1302-93-8)

A4 Not classifiable as a human carcinogen.

SILICA, CRYSTALLINE, CRISTOBALITE (CAS A2 Suspected human carcinogen.

14464-46-1)

Titanium Dioxide (CAS 13463-67-7)

A4 Not classifiable as a human carcinogen.

Canada - Alberta OELs: Carcinogen category

SILICA, CRYSTALLINE, CRISTOBALITE (CAS Suspected human carcinogen.

14464-46-1)

Canada - Manitoba OELs: carcinogenicity

Mullite (CAS 1302-93-8)

Not classifiable as a human carcinogen.

SILICA, CRYSTALLINE, CRISTOBALITE (CAS Suspected human carcinogen.

14464-46-1)

Titanium Dioxide (CAS 13463-67-7)

Not classifiable as a human carcinogen.

Canada - Quebec OELs: Carcinogen category

SILICA, CRYSTALLINE, CRISTOBALITE (CAS Detected carcinogenic effect in animals.

14464-46-1)

IARC Monographs. Overall Evaluation of Carcinogenicity

SILICA, AMORPHOUS, FUMED (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

SILICA, CRYSTALLINE, CRISTOBALITE (CAS 1 Carcinogenic to humans.

14464-46-1)

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

SILICA, CRYSTALLINE, CRISTOBALITE (CAS Known To Be Human Carcinogen.

14464-46-1)

Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

repeated exposure

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsThis product, in its present state, when discarded or disposed of, is not a hazardous waste

according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Hazardous waste codeSince this product is used in several industries, no Waste Code can be provided by the supplier.

The Waste Code should be determined in arrangement with your waste disposal partner or the

responsible authority.

Waste from residues / unused

products

Not available.

Contaminated packaging Not available.

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

Not applicable.

15. Regulatory information

the IBC Code

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

Material name: KAST-O-LITE 22 G PLUS; KAST-O-LITE 22 G PLUS WF

SDS CANADA

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No

Inventory of Existing and New Chemical Substances (ENCS) No Japan Existing Chemicals List (ECL) Korea No New Zealand New Zealand Inventory No **Philippines** Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory No

16. Other information

05-18-2021 Issue date

Version # 01

Disclaimer This information is based on our present knowledge on creation date. However, this shall not

constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.

Product and Company Identification: Product Codes **Revision information**

Composition / Information on Ingredients: Ingredients

Material name: KAST-O-LITE 22 G PLUS; KAST-O-LITE 22 G PLUS WF 5152, 909 Version #: 01 Issue date: 05-18-2021

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).