

Trade Name: Firefly Millboard - FF 650, FF 700, FF 707, FF 800, FF 900, FF 907, FF 1125

Version: First issued April 2004 Revision Date: 8th June 2016

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1	Product Identifier
	Non-asbestos millboard
	FF 650, FF 700, FF 707, FF 800, FF 900, FF 907, FF1125
1.2	Relevant identified uses of the substance or mixture and uses advised against
	Wide range of applications such as thermal insulation, heat shields and gaskets in high temperature industrial processes and heating systems.
1.3	Details of the supplier of the safety data sheet
	TENMAT Limited Ashburton Road West Trafford Park Manchester M17 1TD United Kingdom
	Tel: +44 (0)161 872 2181 Fax: +44 (0)161 872 7596 Email: sales@tenmat.com
1.4	Emergency telephone number
	+44 (0)161 872 2181 +44 (0)161 955 2446 (24 hours)



Trade Name: Firefly Millboard - FF 650, FF 700, FF 707, FF 800, FF 900, FF 907,

FF 1125

Version: First issued April 2004 Revision Date: 8th June 2016

Section 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]: Not classified.

Classification according to Directive 67/548/EEC or 1999/45/EC: Not classified.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]: Not applicable.

Supplemental hazard information (EU):

These products are not hazardous in the form in which they are shipped by the manufacturer.

However, they may low levels of dust as a result of downstream activities (eg, cutting) that contains low bio-persistence mineral fibres and small amounts of quartz.

FF grades 650, 700, 707, 800, 900 & 907 may contain minimal amounts of quartz as an impurity in a clay raw material.

These products do not contain substances that meet the criteria for PBT or vPvB according to Annex XIII of REACH.

2.3 Other hazards

Mild mechanical irritation to skin, eyes and upper respiratory system may result from exposure, however any effects are usually temporary.

Section 3: Composition/information on ingredients

These products are insulation boards made from varying amounts of low bio-persistence mineral fibres, and binders.



Trade Name: Firefly Millboard - FF 650, FF 700, FF 707, FF 800, FF 900, FF 907, FF 1125

Version: First issued April 2004 Revision Date: 8th June 2016

Section 4: First Aid Measures

4.1 Description of first aid measures

4.1 Description of First Aid Measures

General Information:

The main hazards arise from downstream activities such as cutting and machining.

Following Inhalation:

Avoid breathing dust. If breathing difficulties are experienced whilst machining, remove to fresh air or a ventilated area and seek medical advice.

Following Skin Contact:

If possible, vacuum excessive dust from clothes as well as skin and hair. Wash and clean contaminated skin with soap and clean water. Clothes should be washed professionally.

Following Eye Contact:

In case of eye contact, Irrigate abundantly with water. Seek medical attention.

Following Ingestion:

If small quantities are ingested, seek medical advice.

Self-Protection for First Aider:

Wear suitable personal protective equipment to avoid inhaling dust.

4.2 Most Important Symptoms and Effects, both Acute and Delayed

Symptoms:

No symptoms expected.

Effects:

No effects expected.

4.3 Indication of any Immediate Medical Attention and Special Treatment Needed

Notes for doctor:

None required

Special Treatment:

None required.



Trade Name: **Firefly Millboard - FF 650, FF 700, FF 707, FF 800, FF 900, FF 907, FF 1125**

Version: First issued April 2004 Revision Date: 8th June 2016

Section 5: Fire-fighting measures

5.1	Extinguishing media
	Suitable extinguishing media: Not flammable.
	Unsuitable extinguishing media: Not applicable.
5.2	Special hazards arising from the substance or mixture
	Hazardous combustion products: None.
5.3	Advice for fire-fighters None required.



Trade Name: Firefly Millboard - FF 650, FF 700, FF 707, FF 800, FF 900, FF 907, FF 1125

Version: First issued April 2004 Revision Date: 8th June 2016

Section 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel:

Avoid inhaling dust.

Protective equipment:

Protective clothing should be provided for operators along with protective equipment shown in Section 8.

Emergency procedures:

For emergency responders:

Avoid inhaling dust.

Personal protective equipment:

Protective clothing should be provided along with protective equipment shown in Section 8.

6.2 Environmental precautions

Prevent spread of dust by dampening any dust spillages. Check local regulations before rinsing or flushing to drain.

6.3 Methods and materials for containment and cleaning up

For containment:

Dampen down any dust spillages as soon as possible. Do not allow dust to be dispersed by wind.

For cleaning up:

Remove large pieces of board by hand and use a vacuum cleaner to remove dust. If a brush is used ensure that dust is dampened beforehand.

Do not allow dust to be dispersed by use of compressed air.

Dust and pieces of board should be packaged into impermeable plastic sacks which should be sealed. Such waste should then be disposed of according to local regulations.



Trade Name: Firefly Millboard - FF 650, FF 700, FF 707, FF 800, FF 900, FF 907, FF 1125

Version: First issued April 2004 Revision Date: 8th June 2016

6.4 Reference to other sections

Section 7 for Handling and Storage and Section 8 for protective equipment.

Section 7: Handling and storage

7.1 Precautions for safe handling

Protective measures:

No special protective measures are normally required.

Advice on safe handling:

Fire prevention:

Products are not flammable.

Aerosol and dust generation prevention:

Small amounts of dust may be generated if boards are allowed to abrade against each other.

Environmental precautions:

No special precautions are required.

Advice on general occupational hygiene:

Wear protective clothing.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Both un-machined and machined boards should be packed to prevent movement, abrasion during transit and absorption of water.

Otherwise normal safe precautions for storage can be used.

To avoid damage and distortion, store on a smooth level surface, in a fully supported position off the ground and in a dry place.

Packaging materials:

Card cartons.

Requirements for storage rooms and vessels:

Dry location.

Hints on storage assembly:



Trade Name: Firefly Millboard - FF 650, FF 700, FF 707, FF 800, FF 900, FF 907, FF 1125

Version: First issued April 2004 Revision Date: 8th June 2016

Millboards are not considered to be dense materials but care should be taken not to exceed safe working loads for equipment and storage shelves or racks.

Storage class:

N/A

Materials to avoid:

No special requirements.

Further information on storage conditions:

N/A

7.3 Specific end uses:

Recommendations:

N/A

Specific end uses:

See references to dust hazards during cutting and machining, Section 4.

Section 8: Exposure controls/personal protection

8.1	Control Parameters Reference should be made to local and country-specific occupational exposure limits for dust, quartz and low bio-persistence mineral fibres. UK monitoring methods can be found as follows:
	MDHS 14/4 – General methods of sampling and gravimetric analysis of thoracic and inhalable aerosols. MDHS 59 – Machine- made fibres airborne number concentration and classification by phase contrast light microscopy. MDHS 101 – Crystalline silica in respirable airborne dusts.
	NIOSH 0500 – Particulates not otherwise regulated, total NIOSH 0600 – Particulates not otherwise regulated, respirable. NIOSH 7400 – Asbestos and other fibres by PCM NIOSH 7500 - Silica, crystalline, by XRD.
8.2	Exposure Controls Fit and use appropriate local exhaust ventilation systems for cutting and machining



Trade Name: **Firefly Millboard - FF 650, FF 700, FF 707, FF 800, FF 900, FF 907, FF 1125**

Version: First issued April 2004 Revision Date: 8th June 2016

operations.
Maintain a clean workplace using a vacuum cleaner.

Section 9: Physical and chemical properties

9.1 Information on Basic Physical and Chemical Properties

Physical State	Solid material
Appearance	Board
Colour	FF700 - yellow
	FF650/707 – buff
	FF800 – pink
	FF900/907 – buff
	FF1125 - buff
Odour	N/A
Odour threshold	N/A
рН	N/A
Melting/Freezing Point	See Tenmat Technical Brochure for
	maximum working temperatures
Boiling point	N/A
Flash point	N/A
Evapouration rate	N/A
Flammability (solid, gas)	N/A
Upper/lower flammability or explosive limits	N/A
Upper explosive limit	N/A
Lower explosive limit	N/A
Vapour pressure	N/A
Vapour density	N/A
Relative density	600 to 1100 kg.m ³
Solubility	Not soluble in water
Partition coefficient n-octanol/water	N/A
Auto-ignition temperature	N/A
Decomposition temperature	N/A
Dynamic viscosity	N/A
Kinematic viscosity	N/A
Explosive properties	N/A
Oxidising properties	N/A



Trade Name: Firefly Millboard - FF 650, FF 700, FF 707, FF 800, FF 900, FF 907, FF 1125

Version: First issued April 2004 Revision Date: 8th June 2016

Section 10: Stability and reactivity

10.1	Reactivity
	Stable and non-reactive
10.2	Chemical Stability
	Stable and inert.
10.3	Possibility of Hazardous Reaction
	There is the possibility of release of gaseous oxidation products from organic binders during
	initial heating up to around 400 °C. It is recommended that the work area is ventilated until the oxidation product gases have dispersed.
	the oxidation product gases have dispersed.
10.4	Conditions to Avoid
	Exposure to water.
10.5	Incompatible Materials
	None.
10.6	Hazardous Decomposition Products
	None.

Section 11: Toxicological Information

11.1 Information on Toxicological Effects

Exposure is mainly to low levels of dusts generated during downstream activities such as cutting and machining.

Low bio-persistence mineral fibres as used in these products have been developed to be quickly and effectively cleared from lung tissues.

Repeated or prolonged inhalation of crystalline quartz may cause delayed lung damage.

Acute Effects

Acute Inhalation Toxicity	Nose and throat irritation
Skin Irritation	Mild irritation
Eye Irritation	Irritation

Chronic Effects

Respiratory or Skin Sensitisation	Irritation of both the respiratory tract and skin is by
	mechanical means and is not the result of an
	allergic reaction or chemical damage.



Trade Name: Firefly Millboard - FF 650, FF 700, FF 707, FF 800, FF 900, FF 907, FF 1125

Version: First issued April 2004 Revision Date: 8th June 2016

Section 12: Ecological Information

12.1	Toxicity Millboard products are insoluble in water and remain stable over time. The major constituents are similar in their chemical composition to naturally occurring clays and minerals.
12.2	Persistence and Degradability Not established.
12.3	Bio-accumulative Potential Not established.
12.4	Mobility in Soil No information available.
12.5	Results of PBT and vPvB Assessment These products do not contain substances that are considered as either PBT or vPvB.
12.6	Other Adverse Effects No other additional information available.

Section 13: Disposal Considerations

13.1	Waste Treatment Methods
	Product/Packaging Disposal: Packaging can be cleaned and recycled.
	Waste Treatment Options: Waste from these products may be disposed of in landfill according to local regulations.



Trade Name: **Firefly Millboard - FF 650, FF 700, FF 707, FF 800, FF 900, FF 907, FF 1125**

Version: First issued April 2004 Revision Date: 8th June 2016

Section 14: Transport Information

14.1	UN Number
	N/A
14.2	UN Proper Shipping Name N/A
14.3	Transport Hazard Class(es) N/A Hazard Labels
14.4	Packing Group N/A
14.5	Environmental Hazards N/A
14.6	Special Precautions for User N/A
14.7	Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code N/A



Trade Name: **Firefly Millboard - FF 650, FF 700, FF 707, FF 800, FF 900, FF 907, FF 1125**

Version: First issued April 2004 Revision Date: 8th June 2016

Section 15: Regulatory Information

15.1	Safety, Health and Environmental Regulations/Legislation Specific for the Substance or Mixture
	EU Regulations Regulation (EC) No 1907/2006, 18 th December 2006, on Regulation, Evaluation, Authorisation and Restriction of Chemicals (REACH)
	Regulation (EC) No 1272/2008, 20 th January 2009, on Classification, Labelling and Packaging of Substances and Mixtures (OJL 353)
	The 7 th Adaptation to Technical Progress (ATP) to Regulation (EC) No 1272/2008 was published on 15 th July 2015.
	Worker Protection In accordance with the following directives and their amendments:
	Council Directive 89/391/EEC, 12 th June 1989 on the Introduction of measures to encourage improvements in the safety and health of workers at work
	Council Directive 98/24/EC, 7 th April 1998 on the Protection of workers from the risks related to chemical agents at work.
15.2	Chemical Safety Assessment Available on request.



Trade Name: **Firefly Millboard - FF 650, FF 700, FF 707, FF 800, FF 900, FF 907, FF 1125**

Version: First issued April 2004 Revision Date: 8th June 2016

Section 16: Other Information

16.1	Indication of Changes
	All sections updated 31st May 2016
	Product FF 1125 added to Product List
	Section 1.3 amended to include corrected post code
16.2	Abbreviations and Acronyms
	None used.
16.3	Key Literature References and Sources of Data
	See main sections.
16.4	Classification for Mixtures and Used Evaluation Method According to Regulation (EC) 1207/2008 [CLP] See Section 2.
16.5	Relevant R-, H- and EUH Phrases (Number and Text)
	N/A
16.6	Training Advice
	See Tenmat Millboard Products Technical Brochure for information on use.
16.7	Further Information
	For further information visit <u>www.tenmat.com</u>