⋘ HWI

SAFETY DATA SHEET

1. Identification

Product identifier GREENLITE-45-L AL; GREENLITE-45-L AL PLUS

Other means of identification

Brand Code 5517, 5518

Recommended use For Industrial or Professional Use Only

Recommended restrictionsAvoid dry cutting, blasting, or dust generation. Users should be informed of the potential presence

of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under

applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name HarbisonWalker International

Address 1305 Cherrington Parkway, Suite 100

Moon Township Pennsylvania 15108

US

Telephone General Phone: 412-375-6600

Websitewww.thinkHWI.comEmergency phone numberNot available.SupplierNot available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 1A

Specific target organ toxicity, repeated

exposure

Environmental hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer. Causes damage to organs through prolonged or repeated exposure.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Category 1

Response Get medical advice/attention if you feel unwell.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental informationUsers should be informed of the potential presence of respirable dust and respirable crystalline

silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and

handling of this material should be provided as required under applicable regulations.

3. Composition/information on ingredients

Mixtures

Material name: GREENLITE-45-L AL; GREENLITE-45-L AL PLUS 5517, 5518 Version #: 01 Issue date: 08-07-2019

Chemical name	Common name and synonyms	CAS number	%
Cement, Alumina, Chemicals		65997-16-2	20 - 40
Mullite		1302-93-8	10 - 25
Barium Sulfate		7727-43-7	2.5 - 10
SILICA, AMORPHOUS, FUMED		69012-64-2	2.5 - 10
SILICA, AMORPHOUS, FUMED	Fumed Silica Silica, crystalline free	7631-86-9	2.5 - 10
SILICA, CRYSTALLINE, CRISTOBALITE		14464-46-1	2.5 - 10
SILICA, CRYSTALLINE, QUARTZ		14808-60-7	2.5 - 10
Titanium Dioxide		13463-67-7	0.1 - 2.5
Other components below reportable levels			20 - 40

Crystalline silica may be present at low concentrations; most of this is encapsulated in the coarse aggregate or as part of the clays or sands.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Wash off with soap and water. Get medical attention if irritation develops and persists. Skin contact Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and

delayed

Dusts may irritate the respiratory tract, skin and eyes. Prolonged exposure may cause chronic

effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible).

5. Fire-fighting measures

Suitable extinguishing media

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media

Not applicable.

Specific hazards arising from the chemical

Not available.

Not available.

Special protective equipment

and precautions for firefighters

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Collect dust using a vacuum cleaner equipped with HEPA filter. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	Туре	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	10 mg/m3	
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable.
		0.025 mg/m3	Respirable particles.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Total dust.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable.
SILICA, AMORPHOUS, FUMED (CAS 7631-86-9)	TWA	4 mg/m3	Total
SILICA, AMORPHOUS, FUMED (CAS 69012-64-2)	TWA	4 mg/m3	Total fume.
SILICA, AMORPHOUS, FUMED (CAS 7631-86-9)	TWA	1.5 mg/m3	Respirable.
SILICA, AMORPHOUS, FUMED (CAS 69012-64-2)	TWA	1.5 mg/m3	Respirable fume.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	3 mg/m3	Respirable fraction.

Components	Type	Value	Form
		10 mg/m3	Total dust.
	217/2006, The Workplace Safety		Form
Components	Type	Value	
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.025 mg/m3	Respirable fraction.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
	ol of Exposure to Biological or C		_
Components	Туре	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	10 mg/m3	
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
SILICA, AMORPHOUS, FUMED (CAS 69012-64-2)	TWA	2 mg/m3	Respirable fraction.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable fraction.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
	try of Labor - Regulation respec	ting occupational health and sa	fety)
Components	Туре	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
SILICA, AMORPHOUS, FUMED (CAS 7631-86-9)	TWA	6 mg/m3	Respirable dust.
SILICA, AMORPHOUS, FUMED (CAS 69012-64-2)	TWA	2 mg/m3	Respirable dust and/o fume.
SILICA, CRYSTALLINE, CRISTOBALITE (CAS 14464-46-1)	TWA	0.05 mg/m3	Respirable dust.
SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable dust.
Titanium Dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Total dust.
ogical limit values	No biological exposure limits noted	for the ingredient(s).	
	Occupational exposure to nuisance should be monitored and controlled and respirable crystalline silica sho	d. Occupational exposure to nuisa	
trols s	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below to Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.		

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Use of an impervious apron is recommended.

exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.









General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state
Form
Color
Not available.

Odor threshold
PH
Not available.

Melting point/freezing point
Not available.
Not available.

Initial boiling point and boiling range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Explosive properties Not explosive.

Oxidizing properties Not oxidizing.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Powerful oxidizers. Chlorine.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Dust may irritate respiratory system. Prolonged inhalation may be harmful.

Skin contact Dust or powder may irritate the skin.

Eve contact Dust may irritate the eyes.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Dusts may irritate the respiratory tract, skin and eyes.

Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

SILICA, CRYSTALLINE, CRISTOBALITE (CAS Irritant

14464-46-1)

Titanium Dioxide (CAS 13463-67-7) Irritant

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica

inhaled from occupational sources can cause lung cancer in humans. However in making the

overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker

protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

ACGIH Carcinogens

Mullite (CAS 1302-93-8)

A4 Not classifiable as a human carcinogen.

SILICA, CRYSTALLINE, CRISTOBALITE (CAS A2 Suspected human carcinogen.

14464-46-1)

SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7) A2 Suspected human carcinogen.

Titanium Dioxide (CAS 13463-67-7)

A4 Not classifiable as a human carcinogen.

Canada - Alberta OELs: Carcinogen category

SILICA, CRYSTALLINE, CRISTOBALITE (CAS Suspected human carcinogen.

14464-46-1)

SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7) Suspected human carcinogen.

Material name: GREENLITE-45-L AL; GREENLITE-45-L AL PLUS 5517, 5518 Version #: 01 Issue date: 08-07-2019

Canada - Manitoba OELs: carcinogenicity

Mullite (CAS 1302-93-8)

Not classifiable as a human carcinogen.

SILICA, CRYSTALLINE, CRISTOBALITE (CAS Suspected human carcinogen.

14464-46-1)

SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7) Suspected human carcinogen.

Titanium Dioxide (CAS 13463-67-7)

Not classifiable as a human carcinogen.

Canada - Quebec OELs: Carcinogen category

SILICA, CRYSTALLINE, CRISTOBALITE (CAS Detected carcinogenic effect in animals.

14464-46-1)

SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7) Suspected carcinogenic effect in humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

SILICA, AMORPHOUS, FUMED (CAS 69012-64-2)
3 Not classifiable as to carcinogenicity to humans.
SILICA, AMORPHOUS, FUMED (CAS 7631-86-9)
3 Not classifiable as to carcinogenicity to humans.

SILICA, CRYSTALLINE, CRISTOBALITE (CAS 1 Carcinogenic to humans.

14464-46-1)

SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7) 1 Carcinogenic to humans.

Titanium Dioxide (CAS 13463-67-7) 2B Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens

SILICA, CRYSTALLINE, CRISTOBALITE (CAS Known To Be Human Carcinogen.

14464-46-1)

Reasonably Anticipated to be a Human Carcinogen.

SILICA, CRYSTALLINE, QUARTZ (CAS 14808-60-7) Known To Be Human Carcinogen.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Developmental effects

SILICA, CRYSTALLINE, QUARTZ 0

Developmental effects - EU category

SILICA, CRYSTALLINE, QUARTZ 0

Embryotoxicity

SILICA, CRYSTALLINE, QUARTZ 0

Reproductivity

SILICA, CRYSTALLINE, QUARTZ 0

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be

harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsThis product, in its present state, when discarded or disposed of, is not a hazardous waste

according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Hazardous waste codeSince this product is used in several industries, no Waste Code can be provided by the supplier.

The Waste Code should be determined in arrangement with your waste disposal partner or the

responsible authority.

Waste from residues / unused

products

Not available.

Contaminated packaging Not available.

Material name: GREENLITE-45-L AL; GREENLITE-45-L AL PLUS 5517, 5518 Version #: 01 Issue date: 08-07-2019

14. Transport information

TDG

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

Canadian regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

Toxic Substances Control Act (TSCA) Inventory

16. Other information

Issue date 08-07-2019

5517, 5518 Version #: 01 Issue date: 08-07-2019

Version # 01

United States & Puerto Rico

Material name: GREENLITE-45-L AL; GREENLITE-45-L AL PLUS

No

This information is based on our present knowledge on creation date. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid Disclaimer

contractual relationship.

Product and Company Identification: Product Codes **Revision information**

Composition / Information on Ingredients: Ingredients

Material name: GREENLITE-45-L AL; GREENLITE-45-L AL PLUS SDS CANADA 9/9