# HarbisonWalker

## SAFETY DATA SHEET

1. Identification

Product identifier INSWOOL-HP BULK; INSWOOL-HP BLANKET 4#, 6#, 8#, 10#; INSWOOL-HP BLANKET FOIL

BACK; INSWOOL-HP MODULE CM; INSWOOL-HP TRIM

Other means of identification

Brand Code 5830, 5826, 5827, 5828, 5824, 5829, 5831, 5835, 5825, 099C, 119C

Recommended use For Industrial or Professional Use Only • Primary Use: Refractory Ceramic Fiber (RCF) materials

are used primarily in industrial high temperature insulating applications. Examples include heat shields, heat containment, gaskets, expansion joints, industrial furnaces, ovens, kilns, boilers and other process equipment at applications up to 1400°C. RCF based products are not intended for direct sale to the general public. While RCFs are used in the manufacture of some consumer products, such as catalytic converter mats and wood burning stoves, the materials are contained, encapsulated, or bonded within the units. • Secondary Use: Conversion into wet and dry mixtures and articles (refer to section 8). • Tertiary Use: Installation, removal (industrial and professional)

Maintenance and service life (industrial and professional) (refer to section 8).

**Recommended restrictions** Avoid dry cutting, blasting, or dust generation.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name HarbisonWalker International

Address 1305 Cherrington Parkway, Suite 100

Moon Township Pennsylvania 15108

US

**Telephone** General Phone: 412-375-6600

Website www.thinkHWI.com

Emergency phone number CHEMTREC 24 HOUR 1-800-424-9300

EMERGENCY #

Supplier Not available.

2. Hazard identification

Physical hazards Not classified.

Health hazards Carcinogenicity Category 2

Environmental hazards Not classified.

Label elements



Signal word Warning

**Hazard statement** Suspected of causing cancer.

**Precautionary statement** 

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Wear protective gloves/protective clothing/eye protection/face protection.

**Response** IF exposed or concerned: Get medical advice/attention.

**Storage** Store away from incompatible materials.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards None known.

Supplemental information None.

## 3. Composition/information on ingredients

Mixtures

 Chemical name
 Common name and synonyms
 CAS number
 %

 FIBROUS GLASS
 REFRACTORY CERAMIC FIBER/FIBRE (RCF)
 142844-00-6
 80 - 100

 High Temperature Insulation Wool (HTIW) SYNTHETIC VITREOUS FIBERS (SVF)
 Nan-Made Mineral Fiber (MMMF)
 Man-Made Vitreous Fiber (MMVF)

 Alumino Silicate Wool (ASW)

**Composition comments** 

This product contains Refractory Ceramic Fibers (RCF) or an RCF wrap or mat. IARC has classified RCFs as a possible human carcinogen, Group 2B. This classification was based on sufficient evidence of carcinogenicity in animals and no available data in humans. NTP classified respirable RCFs as reasonably anticipated carcinogens. The final report of the USA mortality study was issued in 2017 (LeMasters et al., in press). The study concluded that "after 30 years of follow-up, no excess of lung cancers in the mortality study and no significant association with radiographic findings of interstitial fibrosis were found in this group of workers." The study also found a small incidence of other effects that appear unrelated to RCF exposure. The final mortality report did not change the current hazard classification for RCF. HWI recommends that safe handling methods are followed, including air monitoring in areas wherever the potential exists for airborne fibers, minimizing airborne exposures through use of NIOSH approved respirators, and wearing protective clothing, gloves, and eye protection. For additional information please visit www.htiwcoalition.org Please review the workplace guidelines for additional handling information.

## 4. First-aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.

**Eye contact** Rinse with water. Get medical attention if irritation develops and persists.

IngestionRinse mouth. Get medical attention if symptoms occur.Most importantDirect contact with eyes may cause temporary irritation.

symptoms/effects, acute and

delayed Indication of immediate

medication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

Use fire-extinguishing media appropriate for surrounding materials.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

**General information** 

Not available.

Specific hazards arising from

the chemical

Not applicable.

Special protective equipment and precautions for firefighters

Not available.

## 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

## **Occupational exposure limits**

Components	Туре	ule 1, Table 2) Value	Form
FIBROUS GLASS (CAS 142844-00-6)	TWA	0.2 fibers/cm3	Fiber.
,		5 mg/m3	Total particulate.
		5 mg/m3	Fiber, total
Canada. British Columbia Safety Regulation 296/97,	OELs. (Occupational Exposure Limits fo as amended)	r Chemical Substances, Oc	cupational Health and
Components	Туре	Value	Form
FIBROUS GLASS (CAS 142844-00-6)	TWA	0.2 fibers/cm3	Fiber.
		5 mg/m3	Inhalable fibers.
	Reg. 217/2006, The Workplace Safety And	·-	_
Components	Туре	Value	Form
FIBROUS GLASS (CAS 142844-00-6)	TWA	5 mg/m3	Inhalable fraction.
Canada. Ontario OELs. (Components	ontrol of Exposure to Biological or Chem Type	nical Agents) Value	Form
FIBROUS GLASS (CAS 142844-00-6)	TWA	0.5 fibers/ml	Respirable fibers.
		5 mg/m3	Inhalable fraction.
Canada. Quebec OELs. (M Components	linistry of Labor - Regulation respecting Type	occupational health and saf Value	ety) Form
FIBROUS GLASS (CAS 142844-00-6)	TWA	1 fibers/cm3n	Fiber.
		10 mg/m3	fibers, total dust
logical limit values	No biological exposure limits noted for t	he ingredient(s).	
logical limit values posure guidelines	Recommended Exposure Guideline 0.5 RCF in the U.S. OSHA's "Particulate Not 1910.1000, Subpart Z, Air Contaminant Fraction 5 mg/m3. The High Tempera comprehensive toxicology and epidemic [see Section 11 for more details], consuconducted a thorough review of the RC in a state-of-the-art quantitative risk ass OSHA PEL, HTIW has adopted a reconmethod 7400B. The manufacturers' REthrough prudent exposure control and refeasibility as determined by extensive in an agreement with the U.S. Occupation OCCUPATIONAL EXPOSURE LEVELS evaluation of occupational exposure lim	he ingredient(s).  Fiber/CC There is no specificated (PNO s] applies generally; Total Dusture Insulation Wool Coalition blogy studies to identify potential experts familiar with fiber F-related scientific literature, a sessment. Based on these efformended exposure guideline, G is intended to promote occupation and it reflects relative adustrial hygiene monitoring eral Safety and Health Administ S (OEL) Non-regulatory OEL its and determining their relative to the second seco	ic regulatory standard for R)" standard [29 CFR st 15 mg/m3; Respirable (HTIW) has sponsored tial RCF-related health effer and particle science, and further evaluated the datas measured under NIOSH pational health and safety extechnical and economic forts undertaken pursuant ration (OSHA). OTHER decisions also vary. The ve applicability to the
	Recommended Exposure Guideline 0.5 RCF in the U.S. OSHA's "Particulate Not 1910.1000, Subpart Z, Air Contaminant Fraction 5 mg/m3. The High Tempera comprehensive toxicology and epidemic [see Section 11 for more details], consuconducted a thorough review of the RC in a state-of-the-art quantitative risk ass OSHA PEL, HTIW has adopted a recommethod 7400B. The manufacturers' REthrough prudent exposure control and refeasibility as determined by extensive in an agreement with the U.S. Occupation OCCUPATIONAL EXPOSURE LEVELS	he ingredient(s).  Fiber/CC There is no specific Otherwise Regulated (PNO is] applies generally; Total Dusture Insulation Wool Coalition blogy studies to identify potentiated experts familiar with fiber F-related scientific literature, a essment. Based on these efformended exposure guideline, G is intended to promote occupation and it reflects relative adustrial hygiene monitoring eral Safety and Health Administ S (OEL) Non-regulatory OEL its and determining their relative and the same determining their relative to the same determining the same determining their relative to the same determining the sam	ic regulatory standard for R)" standard [29 CFR st 15 mg/m3; Respirable (HTIW) has sponsored tial RCF-related health effer and particle science, and further evaluated the dates and in the absence of a sameasured under NIOSH pational health and safety extechnical and economic fforts undertaken pursuant ration (OSHA). OTHER decisions also vary. The ve applicability to the Industrial Hygienist.
propriate engineering	Recommended Exposure Guideline 0.5 RCF in the U.S. OSHA's "Particulate Not 1910.1000, Subpart Z, Air Contaminant Fraction 5 mg/m3. The High Tempera comprehensive toxicology and epidemic [see Section 11 for more details], consuconducted a thorough review of the RC in a state-of-the-art quantitative risk ass OSHA PEL, HTIW has adopted a recommethod 7400B. The manufacturers' REI through prudent exposure control and reasibility as determined by extensive ir an agreement with the U.S. Occupation OCCUPATIONAL EXPOSURE LEVELS evaluation of occupational exposure limworkplace is best performed, on a case Good general ventilation (typically 10 ai should be matched to conditions. If appor other engineering controls to maintain	he ingredient(s).  Fiber/CC There is no specific to Otherwise Regulated (PNOs) applies generally; Total Dusture Insulation Wool Coalition blogy studies to identify potential texture, a sessment. Based on these efformended exposure guideline, G is intended to promote occupeduction and it reflects relative adustrial hygiene monitoring eral Safety and Health Administ (OEL) Non-regulatory OEL its and determining their relative rehanges per hour) should be licable, use process enclosure a airborne levels below recomed, maintain airborne levels to	ic regulatory standard for R)" standard [29 CFR st 15 mg/m3; Respirable (HTIW) has sponsored tial RCF-related health effer and particle science, and further evaluated the day as measured under NIOSH pational health and safety etechnical and economic forts undertaken pursuant ration (OSHA). OTHER decisions also vary. The ve applicability to the Industrial Hygienist. et used. Ventilation rates es, local exhaust ventilation mended exposure limits. If o an acceptable level.
propriate engineering ntrols	Recommended Exposure Guideline 0.5 RCF in the U.S. OSHA's "Particulate Not 1910.1000, Subpart Z, Air Contaminant Fraction 5 mg/m3. The High Tempera comprehensive toxicology and epidemic [see Section 11 for more details], consuconducted a thorough review of the RC in a state-of-the-art quantitative risk ass OSHA PEL, HTIW has adopted a recommethod 7400B. The manufacturers' REthrough prudent exposure control and reasibility as determined by extensive ir an agreement with the U.S. Occupation OCCUPATIONAL EXPOSURE LEVELS evaluation of occupational exposure lim workplace is best performed, on a case Good general ventilation (typically 10 ai should be matched to conditions. If app or other engineering controls to maintail exposure limits have not been establish s, such as personal protective equipments.	he ingredient(s).  Fiber/CC There is no specific to Otherwise Regulated (PNOs) applies generally; Total Dusture Insulation Wool Coalition blogy studies to identify potential texture, a sessment. Based on these efformended exposure guideline, G is intended to promote occupeduction and it reflects relative adustrial hygiene monitoring eral Safety and Health Administ (OEL) Non-regulatory OEL its and determining their relative rehanges per hour) should be licable, use process enclosure a airborne levels below recomed, maintain airborne levels to	ic regulatory standard for R)" standard [29 CFR st 15 mg/m3; Respirable (HTIW) has sponsored tial RCF-related health effer and particle science, and further evaluated the day as measured under NIOSH pational health and safety etechnical and economic forts undertaken pursuant ration (OSHA). OTHER decisions also vary. The ve applicability to the Industrial Hygienist. et used. Ventilation rates es, local exhaust ventilation mended exposure limits. If o an acceptable level.
propriate engineering ntrols  ividual protection measures Eye/face protection	Recommended Exposure Guideline 0.5 RCF in the U.S. OSHA's "Particulate Not 1910.1000, Subpart Z, Air Contaminant Fraction 5 mg/m3. The High Tempera comprehensive toxicology and epidemic [see Section 11 for more details], consuconducted a thorough review of the RC in a state-of-the-art quantitative risk ass OSHA PEL, HTIW has adopted a recommethod 7400B. The manufacturers' REthrough prudent exposure control and reasibility as determined by extensive ir an agreement with the U.S. Occupation OCCUPATIONAL EXPOSURE LEVELS evaluation of occupational exposure lim workplace is best performed, on a case Good general ventilation (typically 10 ai should be matched to conditions. If app or other engineering controls to maintail exposure limits have not been establish s, such as personal protective equipments.	he ingredient(s).  Fiber/CC There is no specific to Otherwise Regulated (PNO is) applies generally; Total Dusture Insulation Wool Coalition Dlogy studies to identify potential ted experts familiar with fiber F-related scientific literature, a ressment. Based on these efformended exposure guideline, G is intended to promote occupeduction and it reflects relative adustrial hygiene monitoring eral Safety and Health Administ (OEL) Non-regulatory OEL its and determining their relatively-case basis, by a qualified r changes per hour) should be licable, use process enclosure in airborne levels below recomed, maintain airborne levels to the deshields are recommended	ic regulatory standard for R)" standard [29 CFR st 15 mg/m3; Respirable (HTIW) has sponsored tial RCF-related health effer and particle science, and further evaluated the day as measured under NIOSH pational health and safety etechnical and economic forts undertaken pursuant ration (OSHA). OTHER decisions also vary. The ve applicability to the Industrial Hygienist. et used. Ventilation rates es, local exhaust ventilation mended exposure limits. If o an acceptable level.

exceeding the exposure limits.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.







General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

**Appearance** 

Physical state Solid.

Form Pressed fibrous material panel

Color Not available.

Odor Not available.

Odor threshold Not available.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling Not available.

range

Flash point Not available.

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Not available.

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

## 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

Incompatible materials Strong oxidizing agents.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure.

Hazardous decomposition

products

No hazardous decomposition products are known.

## 11. Toxicological information

## Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

**Ingestion** Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

## Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Canada - Alberta OELs: Irritant

FIBROUS GLASS (CAS 142844-00-6) Irritant

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

**ACGIH Carcinogens** 

FIBROUS GLASS (CAS 142844-00-6)

A2 Suspected human carcinogen.

Canada - Alberta OELs: Carcinogen category

FIBROUS GLASS (CAS 142844-00-6) Suspected human carcinogen.

Canada - Manitoba OELs: carcinogenicity

FIBROUS GLASS (CAS 142844-00-6) Suspected human carcinogen.

Canada - Quebec OELs: Carcinogen category

FIBROUS GLASS (CAS 142844-00-6)

Detected carcinogenic effect in animals.

IARC Monographs. Overall Evaluation of Carcinogenicity

FIBROUS GLASS (CAS 142844-00-6) 2B Possibly carcinogenic to humans.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

## 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability 
No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

This product, in its present state, when discarded or disposed of, is not a hazardous waste **Disposal instructions** 

> according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

Since this product is used in several industries, no Waste Code can be provided by the supplier. Hazardous waste code

The Waste Code should be determined in arrangement with your waste disposal partner or the

responsible authority.

Waste from residues / unused

products

Not available.

Contaminated packaging Not available.

## 14. Transport information

#### **TDG**

Not regulated as dangerous goods.

#### IATA

Not regulated as dangerous goods.

#### **IMDG**

Not regulated as dangerous goods.

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

## 15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

#### **Controlled Drugs and Substances Act**

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

#### **Greenhouse Gases**

Not listed.

## **Precursor Control Regulations**

Not regulated.

#### International regulations

#### **Stockholm Convention**

Not applicable.

#### **Rotterdam Convention**

Not applicable.

## **Kyoto protocol**

Not applicable.

#### **Montreal Protocol**

Not applicable.

## **Basel Convention**

Not applicable.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes

Country(s) or region Inventory name On inventory (yes/no)\*

New Zealand New Zealand Inventory

**Philippines** Philippine Inventory of Chemicals and Chemical Substances No

(PICCS)

Taiwan Chemical Substance Inventory (TCSI) Taiwan Yes Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico No

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### 16. Other information

Issue date 06-12-2019

Version # 01

Disclaimer This information is based on our present knowledge on creation date. However, this shall not

constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.

Product and Company Identification: Product Codes **Revision information** 

Composition / Information on Ingredients: Ingredients