# SAFETY DATA SHEET



## 1. Identification

**Product identifier BASIC 187 GM-60** 

Other means of identification

**Brand Code** 603A

For Industrial Use Only Recommended use

Avoid dry cutting, blasting, or dust generation. Users should be informed of the potential presence **Recommended restrictions** 

> of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under

applicable regulations.

### Manufacturer/Importer/Supplier/Distributor information

Manufacturer

HarbisonWalker International Company name

**Address** 1305 Cherrington Parkway, Suite 100

Moon Township, Pennsylvania 15108 US

General Phone: 412-375-6600 Telephone

www.thinkHWI.com Website **Emergency phone number** Not available.

# 2. Hazard(s) identification

**Physical hazards** Not classified.

**Health hazards** Skin corrosion/irritation Category 1

> Serious eye damage/eye irritation Category 1 Carcinogenicity Category 1A

Not classified. **Environmental hazards OSHA** defined hazards Not classified.

Label elements



Signal word Danger

Causes severe skin burns and eye damage. Causes serious eye damage. May cause cancer. **Hazard statement** 

**Precautionary statement** 

Obtain special instructions before use. Do not handle until all safety precautions have been read Prevention

and understood. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye

protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all Response

contaminated clothing. Rinse skin with water/shower. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison

center/doctor. Wash contaminated clothing before reuse.

**Storage** Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information Users should be informed of the potential presence of respirable dust and respirable crystalline

silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica (quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and

handling of this material should be provided as required under applicable regulations.

Material name: BASIC 187 GM-60

### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Magnesium Oxide		1309-48-4	50 - 70
Calcium Oxide		1305-78-8	30 - 50
Diiron Trioxide		1309-37-1	2.5 - 10
Silicic Acid, Sodium Salt		1344-09-8	2.5 - 10
Amorphous Silica	Fumed Silica Silica, crystalline free	7631-86-9	1 - 2.5
Bentonite		1302-78-9	0.1 - 2.5
Quartz (SiO2)		14808-60-7	0.1 - 2.5
Other components below reportable levels			0.1 - 2.5

## 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or

poison control center immediately. Chemical burns must be treated by a physician. Wash

contaminated clothing before reuse.

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if Eye contact

Use fire-extinguishing media appropriate for surrounding materials.

present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and

delayed

Ingestion

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. **General information** 

### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Not available.

Specific hazards arising from

the chemical

Not applicable.

Special protective equipment

Not available.

and precautions for firefighters

## 6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Material can be slippery when wet. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

Material name: BASIC 187 GM-60

# 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
Calcium Oxide (CAS 1305-78-8)	PEL	5 mg/m3	
Diiron Trioxide (CAS 1309-37-1)	PEL	10 mg/m3	Fume.
Magnesium Oxide (CAS 1309-48-4)	PEL	15 mg/m3	Total particulate.
Quartz (SiO2) (CAS 14808-60-7)	PEL	0.05 mg/m3	Respirable dust.
US. OSHA Table Z-3 (29 CFR 191	0.1000)		
Components	Type	Value	Form
Amorphous Silica (CAS 7631-86-9)	TWA	0.8 mg/m3	
		20 mppcf	
Diiron Trioxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Magnesium Oxide (CAS 1309-48-4)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	Form
Calcium Oxide (CAS 1305-78-8)	TWA	2 mg/m3	
Diiron Trioxide (CAS 1309-37-1)	TWA	5 mg/m3	Respirable fraction.
Magnesium Oxide (CAS 1309-48-4)	TWA	10 mg/m3	Inhalable fraction.
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Che	mical Hazards		
Components	Туре	Value	Form
Amorphous Silica (CAS 7631-86-9)	TWA	6 mg/m3	

Material name: BASIC 187 GM-60

603A Version #: 01 Issue date: 12-29-2020

**US. NIOSH: Pocket Guide to Chemical Hazards Form** Components Value Type Calcium Oxide (CAS **TWA** 2 mg/m3 1305-78-8) Diiron Trioxide (CAS **TWA** Dust and fume. 5 mg/m3 1309-37-1) Respirable dust. Quartz (SiO2) (CAS **TWA** 0.05 mg/m3 14808-60-7)

No biological exposure limits noted for the ingredient(s). **Biological limit values** 

Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica **Exposure guidelines** 

should be monitored and controlled. Occupational exposure to nuisance dust (total and respirable)

and respirable crystalline silica should be monitored and controlled.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles) and a face shield. Eye/face protection

Skin protection

Wear appropriate chemical resistant gloves. **Hand protection** 

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels Respiratory protection

exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.









General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

#### 9. Physical and chemical properties

#### **Appearance**

Solid. Physical state Solid. **Form** 

Not available. Color Odor Not available. **Odor threshold** Not available. Not available. pН Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

Flash point Not available. Not available. **Evaporation rate** Not available. Flammability (solid, gas)

### Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

603A Version #: 01 Issue date: 12-29-2020

Vapor pressureNot available.Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Contact with incompatible materials.

Incompatible materials Chlorine. Phosphorus.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may

not be specific to industrial application exposure.

**Hazardous decomposition** 

products

No hazardous decomposition products are known.

# 11. Toxicological information

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contactCauses severe skin burns.Eye contactCauses serious eye damage.IngestionCauses digestive tract burns.

Symptoms related to the physical, chemical and toxicological characteristics

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including

blindness could result. Coughing.

Information on toxicological effects

Acute toxicity Not known.

**Skin corrosion/irritation** Causes severe skin burns and eye damage.

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Material name: BASIC 187 GM-60 SDS US

## Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

Amorphous Silica (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans. Diiron Trioxide (CAS 1309-37-1) 3 Not classifiable as to carcinogenicity to humans.

Quartz (SiO2) (CAS 14808-60-7) 1 Carcinogenic to humans.

# OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Quartz (SiO2) (CAS 14808-60-7) Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

Quartz (SiO2) (CAS 14808-60-7) Known To Be Human Carcinogen.

**Reproductive toxicity**This product is not expected to cause reproductive or developmental effects.

**Developmental effects** 

 Quartz (SiO2)
 0

 Developmental effects - EU category
 0

 Quartz (SiO2)
 0

 Embryotoxicity
 0

 Quartz (SiO2)
 0

 Reproductivity
 0

 Quartz (SiO2)
 0

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

#### 12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential Mobility in soil

No data available. No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

**Disposal instructions**This product, in its present state, when discarded or disposed of, is not a hazardous waste

according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria

for hazardous waste.

**Hazardous waste code**Since this product is used in several industries, no Waste Code can be provided by the supplier.

The Waste Code should be determined in arrangement with your waste disposal partner or the

sds us

responsible authority.

Waste from residues / unused

products

Not available.

Contaminated packaging Not available.

Material name: BASIC 187 GM-60
603A Version #: 01 Issue date: 12-29-2020

### 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Transport in bulk according to

Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

## 15. Regulatory information

**US** federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All chemical substances in this product are listed on the TSCA chemical substance inventory where required.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Quartz (SiO2) (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Skin corrosion or irritation

categories Serious eye damage or eye irritation

Carcinogenicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

**California Proposition 65** 

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (SiO2) (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Magnesium Oxide (CAS 1309-48-4) Quartz (SiO2) (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No

Material name: BASIC 187 GM-60 SDS US

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) Yes United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

Philippine Inventory of Chemicals and Chemical Substances

# 16. Other information, including date of preparation or last revision

Issue date 12-29-2020

Version # 01

Philippines

Disclaimer This information is based on our present knowledge on creation date. However, this shall not

constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.

Product and Company Identification: Product and Company Identification **Revision information** 

Toxicological Information: Toxicological Data

Ecological Information: Ecotoxicity

Material name: BASIC 187 GM-60 SDS US

Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).