# International

# SAFETY DATA SHEET

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or **ARMORTECH 65AL** 

designation of the mixture

**Registration number** 

**Synonyms** None **Brand Code** 418B

14-March-2013 **Issue date** 

**Version number** 

**Revision date** 04-September-2019 Supersedes date 12-November-2015

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** For Industrial or Professional Use Only

Uses advised against Avoid dry cutting, blasting, or dust generation.

1.3. Details of the supplier of the safety data sheet

Supplier

Company name HarbisonWalker International

**Address** 1305 Cherrington Parkway, Suite 100

Moon Township, PA 15108, USA

**United States** 

**Division** 

**Telephone** General Phone: 412-375-6743

> CHEMTREC EMERGENCY 1-800-424-9300

US/CAN ONLY

sds@thinkHWI.com e-mail

**Contact person HWI USA** 

1.4. Emergency telephone

number

General Phone: 412-375-6600

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Prolonged exposure may cause chronic effects. Not classified for health hazards. However, **Hazard summary** 

occupational exposure to the mixture or substance(s) may cause adverse health effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

**Hazard pictograms** None Signal word None.

**Hazard statements** The mixture does not meet the criteria for classification.

**Precautionary statements** 

**Prevention** Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

**Disposal** Dispose of waste and residues in accordance with local authority requirements.

Supplemental label

Users should be informed of the potential presence of respirable dust and respirable crystalline information silica as well as their potential hazards. Overexposure to the respirable dust of crystalline silica

(quartz or cristobalite, less than or equal to 5 microns in size) may lead to silicosis in humans, which is a progressive and irreversible lung disease. Appropriate training in the proper use and

handling of this material should be provided as required under applicable regulations.

2.3. Other hazards Not a PBT or vPvB substance or mixture.

## **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Mullite	40 - 60	1302-93-8 215-113-2	-	-	
Classification:					
Cement, Alumina, Chemicals	2,5 - 10	65997-16-2 266-045-5	-	-	
Classification:					
Other components below reportable levels	40 - 60				

# List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

Crystalline silica may be present at low concentrations; most of this is encapsulated in the coarse aggregate or as part of the clays or sands.

**Composition comments** 

The full text for all H-statements is displayed in section 16.

## **SECTION 4: First aid measures**

**General information** Not available.

4.1. Description of first aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Exposure may cause temporary irritation, redness, or discomfort.

**Eye contact** Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both

acute and delayed

4.3. Indication of any

immediate medical attention and special treatment

needed

Treat symptomatically.

# **SECTION 5: Firefighting measures**

**General fire hazards** Not available.

5.1. Extinguishing media

Suitable extinguishing

Use fire-extinguishing media appropriate for surrounding materials.

media

Unsuitable extinguishing

media

Not available.

5.2. Special hazards arising

from the substance or

mixture

Not available.

5.3. Advice for firefighters

**Special protective** equipment for

Not available.

firefighters Special fire fighting

Not available.

procedures

# **SECTION 6: Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

418B Version #: 04 Revision date: 04-September-2019 Issue date: 14-March-2013

For non-emergency

personnel

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

6.4. Reference to other

sections

# **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Avoid prolonged exposure. Observe good industrial hygiene practices.

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the

SDS).

7.3. Specific end use(s)

Not available.

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### **Occupational exposure limits**

Austria. MAK List, OEL Ordinance	e (GwV), BGBI. II, no. 184/2001
Components	Туре

Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	МАК	5 mg/m3	Respirable fume.
		5 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
	STEL	20 mg/m3	Inhalable fraction.
		10 mg/m3	Respirable fume.
		10 mg/m3	Respirable fraction.
Amorphous silica (CAS 7631-86-9)	MAK	4 mg/m3	Inhalable fraction.
Fumes, Silica (CAS 59012-64-2)	MAK	0,3 mg/m3	Respirable fraction.
Fitanium dioxide (CAS 13463-67-7)	MAK	5 mg/m3	Respirable dust.
	STEL	10 mg/m3	Respirable dust.
Belgium. Exposure Limit Value	S.		
Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	1 mg/m3	Respirable fraction.
Amorphous silica (CAS 7631-86-9)	TWA	10 mg/m3	
Barium Sulfate (CAS 7727-43-7)	TWA	10 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

#### Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work Components

Components	туре	value	FOITH
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	3,5 mg/m3	Respirable fraction.
		10 mg/m3	Dust.
		1,5 mg/m3	Respirable fraction.
Amorphous silica (CAS 7631-86-9)	TWA	10 mg/m3	Inhalable fraction.
		0,07 mg/m3	Respirable fraction.
Barium Sulfate (CAS 7727-43-7)	TWA	10 mg/m3	

Material name: ARMORTECH 65AL

SDS EU

418B Version #: 04 Revision date: 04-September-2019 Issue date: 14-March-2013

Components	Туре	Value	Form
Fumes, Silica (CAS 69012-64-2)	TWA	10 mg/m3	Inhalable fraction.
		0,07 mg/m3	Respirable fraction.
Mullite (CAS 1302-93-8)	TWA	2 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Respirable dust.
Croatia. Dangerous Substance 13/09	Exposure Limit Values in the	Workplace (ELVs), Annexes	1 and 2, Narodne Novin
Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	MAC	4 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
Amorphous silica (CAS 7631-86-9)	MAC	6 mg/m3	Total dust.
		2,4 mg/m3	Respirable dust.
Barium Sulfate (CAS 7727-43-7)	MAC	4 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
Fumes, Silica (CAS 69012-64-2)	MAC	6 mg/m3	Total dust.
		2,4 mg/m3	Respirable dust.
Fitanium dioxide (CAS 13463-67-7)	STEL	4 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
Cyprus. OELs. Control of factor amended.	ry atmosphere and dangerous	substances in factories regu	ulation, PI 311/73, as
Components	Туре	Value	
Amorphous silica (CAS 7631-86-9)	TWA	2 mg/m3	

Components	Туре	Value	
Amorphous silica (CAS 7631-86-9)	TWA	2 mg/m3	
Fumes, Silica (CAS 69012-64-2)	TWA	2 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	

# Czech Republic. OELs. Government Decree 361

Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	0,1 mg/m3	Respirable dust.
Amorphous silica (CAS 7631-86-9)	TWA	4 mg/m3	Dust.
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Dust.
Fumes, Silica (CAS 69012-64-2)	TWA	4 mg/m3	Dust.
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Dust.

# **Denmark. Exposure Limit Values**

Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TLV	5 mg/m3	Total
		2 mg/m3	Respirable.
Fumes, Silica (CAS 69012-64-2)	TLV	2 mg/m3	Respirable.

**Denmark. Exposure Limit Values Components Value Form Type** Titanium dioxide (CAS TLV 6 mg/m3 13463-67-7)

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances	. (Annex of Regulation No. 293 of 18
September 2001)	

Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
Amorphous silica (CAS 7631-86-9)	TWA	2 mg/m3	Respirable dust.
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
		1 mg/m3	Dust.
Fumes, Silica (CAS 69012-64-2)	TWA	2 mg/m3	Respirable dust.
Mullite (CAS 1302-93-8)	TWA	2 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	
Finland. Workplace Exposure L	imits		
Components	Туре	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	10 mg/m3	Dust.
Fumes, Silica (CAS 69012-64-2)	TWA	5 mg/m3	
Mullite (CAS 1302-93-8)	TWA	2 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	Dust.
France. Threshold Limit Values Components	s (VLEP) for Occupational Exp Type	oosure to Chemicals in Franc Value	e, INRS ED 984 Form
Aluminium Oxide	VME	10 mg/m3	

(Non-Fibrous) (CAS 1344-28-1)

Regulatory status: Indicative limit (VL)

Barium Sulfate (CAS **VME** 5 mg/m3 Respirable fraction. 7727-43-7)

**Regulatory status:** Regulatory binding (VRC)

Inhalable fraction. 10 mg/m3 Regulatory status: Regulatory binding (VRC)

10 mg/m3

VME

Titanium dioxide (CAS 13463-67-7)

Regulatory status: Indicative limit (VL)

#### Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	4 mg/m3	Inhalable fraction.
		1,5 mg/m3	Respirable fraction.
Amorphous silica (CAS 7631-86-9)	TWA	4 mg/m3	Inhalable fraction.
Barium Sulfate (CAS 7727-43-7)	TWA	4 mg/m3	Inhalable fraction.
		0,3 mg/m3	Respirable fraction.

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Туре	Value	Form
Fumes, Silica (CAS 69012-64-2)	TWA	0,3 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	4 mg/m3	Inhalable dust.
		0,3 mg/m3	Respirable dust.
Germany. TRGS 900, Limit Value Components	s in the Ambient Air at the Workplace Type	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
Amorphous silica (CAS 7631-86-9)	AGW	4 mg/m3	Inhalable fraction.
Barium Sulfate (CAS 7727-43-7)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
Fumes, Silica (CAS 69012-64-2)	AGW	0,3 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	AGW	10 mg/m3	Inhalable fraction.
•		1,25 mg/m3	Respirable fraction.
Greece. OELs (Decree No. 90/199 Components	99, as amended) Type	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	5 mg/m3	Inhalable
,		10 mg/m3	Respirable.
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable.
·		10 mg/m3	Inhalable
Hungary. OELs. Joint Decree on C Components	Chemical Safety of Workplaces Type	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	6 mg/m3	Respirable.
Barium Sulfate (CAS 7727-43-7)	TWA	6 mg/m3	Respirable dust.
•		10 mg/m3	Total inhalable dust
Titanium dioxide (CAS 13463-67-7)	TWA	6 mg/m3	Respirable dust.
•		10 mg/m3	Total inhalable dust
Iceland. OELs. Regulation 154/1	999 on occupational exposure limits Type	Value	Form
Components		10 / 2	
Aluminium Oxide (Non-Fibrous) (CAS	TWA	10 mg/m3	
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Fumes, Silica (CAS	TWA	10 mg/m3 2 mg/m3	Respirable mist.
Components  Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Fumes, Silica (CAS 69012-64-2)  Mullite (CAS 1302-93-8)		_	Respirable mist.

Ireland. Occupational Exposure Limits Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	4 mg/m3	Respirable dust.
,		10 mg/m3	Total inhalable dust.
Amorphous silica (CAS 7631-86-9)	TWA	6 mg/m3	Total inhalable dust.
, , , ,		2,4 mg/m3	Respirable dust.
Barium Sulfate (CAS 7727-43-7)	TWA	2 mg/m3	Respirable dust.
Fumes, Silica (CAS 69012-64-2)	TWA	6 mg/m3	Total inhalable dust.
		2,4 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Total inhalable dust.
Italy. Occupational Exposure Limits Components	Туре	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	1 mg/m3	Respirable fraction.
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Inhalable fraction.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Latvia. OELs. Occupational exposure li Components	mit values of chemical Type	substances in work enviro	nment Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	6 mg/m3	Decomposition aerosol.
1311 20 1)		4 mg/m3	
Amorphous silica (CAS 7631-86-9)	TWA	1 mg/m3	
Barium Sulfate (CAS 7727-43-7)	TWA	2 mg/m3	Dust.
,,		2 mg/m3	
Fumes, Silica (CAS 69012-64-2)	TWA	1 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Lithuania. OELs. Limit Values for Chen Components	nical Substances, Gene Type	eral Requirements Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	5 mg/m3	Inhalable fraction.
1311 23 1)		2 mg/m3	Respirable fraction.
Barium Sulfate (CAS 7727-43-7)	TWA	5 mg/m3	Respirable fraction.
,		10 mg/m3	Inhalable fraction.
		1 mg/m3	Dust.
Mullite (CAS 1302-93-8)	TWA	1 mg/m3	
Mullite (CAS 1302-93-8) Titanium dioxide (CAS	TWA TWA	1 mg/m3 5 mg/m3	

Components	s for Contaminants in the Wor Type	Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TLV	10 mg/m3	
Amorphous silica (CAS 7631-86-9)	TLV	1,5 mg/m3	Respirable dust.
Barium Sulfate (CAS 7727-43-7)	TLV	5 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
Fumes, Silica (CAS 69012-64-2)	TLV	1,5 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	TLV	5 mg/m3	
	abour and Social Policy on 6 J		
and intensities of harmful hea Components	alth factors in the work enviror Type	nment, Journal of Laws 2014 Value	l, item 817 Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	2,5 mg/m3	Inhalable fraction.
		1,2 mg/m3	Respirable fraction.
Amorphous silica (CAS 7631-86-9)	TWA	2 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.
Barium Sulfate (CAS 7727-43-7)	TWA	10 mg/m3	Inhalable fraction.
		1 mg/m3	Respirable fraction.
Titanium dioxide (CAS 13463-67-7)	STEL	30 mg/m3	
	TWA	10 mg/m3	Inhalable fraction.
	pational exposure to chemical Type	agents (NP 1796) Value	
Components	Туре		
Aluminium Oxide (Non-Fibrous) (CAS	TWA	10 mg/m3	
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Barium Sulfate (CAS 7727-43-7)		10 mg/m3	
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Barium Sulfate (CAS	TWA	_	
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Barium Sulfate (CAS 7727-43-7) Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3 10 mg/m3	ce Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Barium Sulfate (CAS 7727-43-7) Titanium dioxide (CAS 13463-67-7) Romania. OELs. Protection of Components Aluminium Oxide (Non-Fibrous) (CAS	TWA  TWA  TWA  workers from exposure to che	10 mg/m3 10 mg/m3 emical agents at the workpla	
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Barium Sulfate (CAS 7727-43-7) Titanium dioxide (CAS 13463-67-7) Romania. OELs. Protection of Components Aluminium Oxide (Non-Fibrous) (CAS	TWA  TWA  TWA  workers from exposure to che Type	10 mg/m3 10 mg/m3 emical agents at the workpla Value	Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Barium Sulfate (CAS 7727-43-7) Titanium dioxide (CAS 13463-67-7) Romania. OELs. Protection of Components Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Titanium dioxide (CAS	TWA  TWA  TWA  Workers from exposure to che Type  STEL	10 mg/m3 10 mg/m3 emical agents at the workpla Value 5 mg/m3	<b>Form</b> Aerosol
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Barium Sulfate (CAS 7727-43-7) Titanium dioxide (CAS 13463-67-7) Romania. OELs. Protection of Components Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Titanium dioxide (CAS	TWA  TWA  TWA  workers from exposure to che Type  STEL  TWA	10 mg/m3 10 mg/m3 emical agents at the workpla Value 5 mg/m3	<b>Form</b> Aerosol
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Barium Sulfate (CAS 7727-43-7) Titanium dioxide (CAS 13463-67-7) Romania. OELs. Protection of Components Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Titanium dioxide (CAS 13463-67-7)	TWA  TWA  TWA  Workers from exposure to che Type  STEL  TWA  STEL	10 mg/m3 10 mg/m3 2 mg/m3 2 mg/m3 15 mg/m3 10 mg/m3	Aerosol Aerosol
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Barium Sulfate (CAS 7727-43-7) Titanium dioxide (CAS 13463-67-7) Romania. OELs. Protection of Components Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Titanium dioxide (CAS 13463-67-7) Slovakia. OELs. Regulation No Components Aluminium Oxide (Non-Fibrous) (CAS	TWA  TWA  TWA  TWA  workers from exposure to che Type  STEL  TWA  STEL  TWA  STEL  TWA  STEL  TWA  SOL 300/2007 concerning protect	10 mg/m3 10 mg/m3 2 mg/m3 2 mg/m3 15 mg/m3 10 mg/m3 2 tion of health in work with o	Aerosol  Aerosol  Chemical agents
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Barium Sulfate (CAS 7727-43-7) Titanium dioxide (CAS 13463-67-7) Romania. OELs. Protection of Components Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Titanium dioxide (CAS 13463-67-7) Slovakia. OELs. Regulation No Components Aluminium Oxide (Non-Fibrous) (CAS	TWA  TWA  TWA  TWA  workers from exposure to che Type  STEL  TWA  TWA  STEL  TWA  TWA  STEL  TWA  TWA  STEL  TWA  TWA  STEL  TWA	10 mg/m3 10 mg/m3 2 mg/m3 2 mg/m3 15 mg/m3 10 mg/m3 2 tion of health in work with o	Form  Aerosol  Aerosol  chemical agents Form
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Barium Sulfate (CAS 7727-43-7) Titanium dioxide (CAS 13463-67-7) Romania. OELs. Protection of Components Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1) Titanium dioxide (CAS 13463-67-7)	TWA  TWA  TWA  TWA  workers from exposure to che Type  STEL  TWA  TWA  STEL  TWA  TWA  STEL  TWA  TWA  STEL  TWA  TWA  STEL  TWA	10 mg/m3 10 mg/m3 2 mg/m3 2 mg/m3 15 mg/m3 10 mg/m3 4 mg/m3	Aerosol  Aerosol  Chemical agents Form  Inhalable fraction.

Components	300/2007 concerning protect Type	Value	Form
Barium Sulfate (CAS 7727-43-7)	TWA	4 mg/m3	Inhalable fraction.
		1,5 mg/m3	Respirable fraction.
Fumes, Silica (CAS 69012-64-2)	TWA	0,3 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	5 mg/m3	
Slovenia. OELs. Regulations con		s against risks due to expo	sure to chemicals while
working (Official Gazette of the Components	Type	Value	Form
Amorphous silica (CAS	TWA	4 mg/m3	Inhalable fraction.
7631-86-9)	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 mg/ms	Timalable fraction.
Fumes, Silica (CAS 69012-64-2)	TWA	4 mg/m3	Inhalable fraction.
Spain. Occupational Exposure Li			
Components	Туре	Value	
Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)	TWA	10 mg/m3	
Barium Sulfate (CAS 7727-43-7)	TWA	10 mg/m3	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m3	
Sweden. OELs. Work Environme Components	ent Authority (AV), Occupation Type	nal Exposure Limit Values ( Value	AFS 2015:7) Form
Aluminium Oxide	TWA	5 mg/m3	Total dust.
(Non-Fibrous) (CAS 1344-28-1)		og,e	
		2 mg/m3	Respirable dust.
1344-28-1)  Barium Sulfate (CAS	TWA	_	
1344-28-1)  Barium Sulfate (CAS	TWA	2 mg/m3	Respirable dust.
1344-28-1)  Barium Sulfate (CAS 7727-43-7)	TWA	2 mg/m3 5 mg/m3	Respirable dust. Respirable dust. Inhalable dust. Total dust.
Barium Sulfate (CAS 7727-43-7) Mullite (CAS 1302-93-8) Titanium dioxide (CAS		2 mg/m3 5 mg/m3 10 mg/m3	Respirable dust. Respirable dust. Inhalable dust.
Barium Sulfate (CAS 7727-43-7) Mullite (CAS 1302-93-8) Titanium dioxide (CAS 13463-67-7) Switzerland. SUVA Grenzwerte a	TWA TWA am Arbeitsplatz	2 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 5 mg/m3	Respirable dust. Respirable dust. Inhalable dust. Total dust. Total dust.
Barium Sulfate (CAS 7727-43-7) Mullite (CAS 1302-93-8) Titanium dioxide (CAS 13463-67-7) Switzerland. SUVA Grenzwerte a	TWA TWA	2 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3	Respirable dust. Respirable dust. Inhalable dust. Total dust.
Barium Sulfate (CAS 7727-43-7)  Mullite (CAS 1302-93-8)  Titanium dioxide (CAS 13463-67-7)  Switzerland. SUVA Grenzwerte a Components  Aluminium Oxide (Non-Fibrous) (CAS	TWA TWA am Arbeitsplatz	2 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 5 mg/m3	Respirable dust. Respirable dust. Inhalable dust. Total dust. Total dust. Form
Barium Sulfate (CAS 7727-43-7)  Mullite (CAS 1302-93-8)  Titanium dioxide (CAS 13463-67-7)  Switzerland. SUVA Grenzwerte a Components  Aluminium Oxide (Non-Fibrous) (CAS	TWA TWA am Arbeitsplatz Type	2 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 5 mg/m3  Value 24 mg/m3	Respirable dust. Respirable dust. Inhalable dust. Total dust. Total dust.  Form  Fume and respirable dust
Barium Sulfate (CAS 7727-43-7)  Mullite (CAS 1302-93-8)  Titanium dioxide (CAS 13463-67-7)  Switzerland. SUVA Grenzwerte a Components  Aluminium Oxide (Non-Fibrous) (CAS	TWA TWA  am Arbeitsplatz Type  STEL	2 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 5 mg/m3	Respirable dust. Respirable dust. Inhalable dust. Total dust. Total dust.  Form  Fume and respirable dust  Respirable dust.
Barium Sulfate (CAS 7727-43-7)  Mullite (CAS 1302-93-8) Titanium dioxide (CAS 13463-67-7)  Switzerland. SUVA Grenzwerte a Components  Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)  Barium Sulfate (CAS	TWA TWA  am Arbeitsplatz Type  STEL	2 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 5 mg/m3  Value 24 mg/m3	Respirable dust. Respirable dust. Inhalable dust. Total dust. Total dust.  Form  Fume and respirable dust  Respirable dust.
	TWA TWA  am Arbeitsplatz Type  STEL  TWA	2 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 5 mg/m3  Value 24 mg/m3 3 mg/m3 3 mg/m3	Respirable dust. Respirable dust. Inhalable dust. Total dust. Total dust.  Form Fume and respirable dust Respirable dust. Fume and respirable dust
Barium Sulfate (CAS 7727-43-7)  Mullite (CAS 1302-93-8)  Titanium dioxide (CAS 13463-67-7)  Switzerland. SUVA Grenzwerte a Components  Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)  Barium Sulfate (CAS 7727-43-7)  Titanium dioxide (CAS	TWA TWA  am Arbeitsplatz Type  STEL  TWA	2 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 5 mg/m3  Value 24 mg/m3 3 mg/m3 3 mg/m3 3 mg/m3	Respirable dust. Respirable dust. Inhalable dust. Total dust. Total dust.  Form  Fume and respirable dust. Respirable dust. Fume and respirable dust. Respirable dust. Respirable dust.
Barium Sulfate (CAS 7727-43-7)  Mullite (CAS 1302-93-8) Titanium dioxide (CAS 13463-67-7)  Switzerland. SUVA Grenzwerte a Components  Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)  Barium Sulfate (CAS	TWA TWA  am Arbeitsplatz Type  STEL  TWA  TWA  TWA	2 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 5 mg/m3  Value 24 mg/m3 3 mg/m3 3 mg/m3 3 mg/m3	Respirable dust. Respirable dust. Inhalable dust. Total dust. Total dust.  Form  Fume and respirable dust. Respirable dust. Fume and respirable dust. Respirable dust. Inhalable dust.
Barium Sulfate (CAS 7727-43-7)  Mullite (CAS 1302-93-8)  Titanium dioxide (CAS 13463-67-7)  Switzerland. SUVA Grenzwerte a Components  Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)  Barium Sulfate (CAS 7727-43-7)  Titanium dioxide (CAS 13463-67-7)  UK. EH40 Workplace Exposure L	TWA TWA  am Arbeitsplatz Type  STEL  TWA  TWA  TWA  TWA  Limits (WELs)	2 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 5 mg/m3  Value 24 mg/m3 3 mg/m3 3 mg/m3 10 mg/m3 3 mg/m3	Respirable dust. Respirable dust. Inhalable dust. Total dust. Total dust.  Form  Fume and respirable dust. Respirable dust. Respirable dust. Respirable dust. Inhalable dust. Respirable dust. Respirable dust.
Barium Sulfate (CAS 7727-43-7)  Mullite (CAS 1302-93-8) Titanium dioxide (CAS 13463-67-7)  Switzerland. SUVA Grenzwerte a Components  Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)  Barium Sulfate (CAS 7727-43-7)  Titanium dioxide (CAS 13463-67-7)  UK. EH40 Workplace Exposure L Components	TWA TWA  am Arbeitsplatz Type  STEL  TWA  TWA  TWA  TWA  TWA  Limits (WELs) Type	2 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 5 mg/m3  Value 24 mg/m3 3 mg/m3 3 mg/m3 10 mg/m3 3 mg/m3 Value	Respirable dust. Respirable dust. Inhalable dust. Total dust. Total dust.  Form  Fume and respirable dust. Respirable dust. Fume and respirable dust.
Barium Sulfate (CAS 7727-43-7)  Mullite (CAS 1302-93-8) Titanium dioxide (CAS 13463-67-7)  Switzerland. SUVA Grenzwerte a Components  Aluminium Oxide (Non-Fibrous) (CAS 1344-28-1)  Barium Sulfate (CAS 7727-43-7)  Titanium dioxide (CAS 13463-67-7)  UK. EH40 Workplace Exposure L Components  Aluminium Oxide (Non-Fibrous) (CAS	TWA TWA  am Arbeitsplatz Type  STEL  TWA  TWA  TWA  TWA  TWA  Limits (WELs) Type	2 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 5 mg/m3  Value 24 mg/m3 3 mg/m3 3 mg/m3 10 mg/m3 3 mg/m3 Value	Respirable dust. Respirable dust. Inhalable dust. Total dust. Total dust.  Form  Fume and respirable dust. Respirable dust. Fume and respirable dust.

UK. EH40 Workplace Exposure Limits (WELs) Components Type		Value	Form
		2,4 mg/m3	Respirable dust.
Barium Sulfate (CAS 7727-43-7)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Inhalable dust.
Fumes, Silica (CAS 69012-64-2)	TWA	6 mg/m3	Inhalable dust.
		2,4 mg/m3	Respirable dust.
Titanium dioxide (CAS 13463-67-7)	TWA	4 mg/m3	Respirable.
		10 mg/m3	Inhalable

**Biological limit values** 

No biological exposure limits noted for the ingredient(s).

**Recommended monitoring** procedures

Follow standard monitoring procedures.

**Derived no effect levels** (DNELs)

Not available.

**Predicted no effect** concentrations (PNECs) Not available.

**Exposure guidelines** Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should

be monitored and controlled.

The resin binder in this product was specifically engineered to have low toxicity, with minima free-phenol (less than 100ppm in this refractory product) and no free-formaldehyde. Under certain conditions, thermal decomposition products may still include carbon monoxide, carbon dioxide, formaldehyde, phenol and aromatic and/or aliphatic compounds.

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should

8.2. Exposure controls

**Appropriate engineering** controls

be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure

limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

**General information** Personal protection equipment should be chosen according to the CEN standards and in discussion

with the supplier of the personal protective equipment.

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

- Hand protection Wear appropriate chemical resistant gloves.

- Other Wear suitable protective clothing.

Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels

exceeding the exposure limits.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.







**Hygiene measures** 

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to

remove contaminants.

**Environmental exposure** 

controls

Environmental manager must be informed of all major releases.

## **SECTION 9: Physical and chemical properties**

# 9.1. Information on basic physical and chemical properties

**Appearance** 

**Physical state** Solid. Solid. **Form** 

Not available. Colour Odour Not available. **Odour threshold** Not available.

7 - 8 pН

Melting point/freezing point Not available. Not available. Initial boiling point and

boiling range

Not available. Flash point **Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Not available.

Flammability limit - lower

(%)

Flammability limit -

upper (%)

Not available.

Vapour pressure Not available. Vapour density Not available. Not available. Relative density

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

**Auto-ignition temperature** Not available. **Decomposition temperature** Not available. Not available. **Viscosity** Not explosive. **Explosive properties Oxidising properties** Not oxidising.

9.2. Other information No relevant additional information available.

# **SECTION 10: Stability and reactivity**

The product is stable and non-reactive under normal conditions of use, storage and transport 10.1. Reactivity

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoid Contact with incompatible materials. Refractories containing crystalline silica may, after service, contain more or less crystalline silica. Care must be taken to avoid and/or control dust from demolition. If in doubt of the proper protection, seek advice from a safety professional.

> The organic binder in this product falls into a class known as phenolic resin. Refractory products using this type of binder are supplied in two forms, (1) shaped products such as brick and (2) monolithics/specialties such as refractory plastics and rams. The hazards associated with phenolic resin are different in the two forms. For pre-cured shapes (brick), the binder has been reacted or polymerized by heat to its solid form prior to shipment. On decomposition by heating, where there is sufficient air and heating rate, the gaseous products are mostly carbon dioxide and water. Under low or limited oxygen supply, decomposition products during heat-up and early service may include phenol, as well as aromatic and/or aliphatic derivatives. After a campaign in service, this refractory product should be completely coked and in that condition the material for disposal would be carbon and an inorganic oxide. During field installation of non-cured unshaped products (monolithics), there is a possibility of exposure to trace amounts of phenol by skin contact and inhalation. After the product has been heated to high temperatures in service, it will have similar decomposition characteristics to pre-cured shapes.

10.5. Incompatible materials Acids. Aluminium. Chlorine. Fluorine. Phosphorus.

Incompatibility is based strictly upon potential theoretical reactions between chemicals and may not

be specific to industrial application exposure.

10.6. Hazardous

decomposition products

No hazardous decomposition products are known.

#### **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

**Inhalation** Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected. **Eve contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

**Symptoms** Exposure may cause temporary irritation, redness, or discomfort.

#### 11.1. Information on toxicological effects

**Acute toxicity** Not known.

Skin corrosion/irritation

Serious eye damage/eye

irritation

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

**Respiratory sensitisation** 

Skin sensitisation

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica Carcinogenicity

inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and

controlled. Risk of cancer cannot be excluded with prolonged exposure.

#### Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

Reproductive toxicity Specific target organ toxicity

- single exposure

Due to partial or complete lack of data the classification is not possible. Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity

- repeated exposure

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible. **Aspiration hazard** 

Mixture versus substance

information

No information available.

Other information This product has no known adverse effect on human health.

# **SECTION 12: Ecological information**

Based on available data, the classification criteria are not met for hazardous to the aquatic 12.1. Toxicity

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative

potential

**Partition coefficient** 

n-octanol/water (log Kow)

Not available.

**Bioconcentration factor (BCF)** 

Not available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and

vPvB assessment

Not a PBT or vPvB substance or mixture. Not available.

12.6. Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Residual waste Not available. Contaminated packaging Not available.

Material name: ARMORTECH 65AL 418B Version #: 04 Revision date: 04-September-2019 Issue date: 14-March-2013 **EU** waste code Not available.

# **SECTION 14: Transport information**

14.1. - 14.6.: Not regulated as dangerous goods.

**RID** 

14.1. - 14.6.: Not regulated as dangerous goods.

**ADN** 

14.1. - 14.6.: Not regulated as dangerous goods.

TATA

14.1. - 14.6.: Not regulated as dangerous goods.

**IMDG** 

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of Not applicable.

Code

MARPOL 73/78 and the IBC

# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **EU** regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

# **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

#### Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

## Other EU regulations

#### Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC)

No 1907/2006, as amended.

**National regulations** Follow national regulation on the protection of workers from the risks of exposure to carcinogens

and mutagens at work, in accordance with Directive 2004/37/EC.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

#### **SECTION 16: Other information**

List of abbreviations Not available. Not available. References Information on evaluation

method leading to the classification of mixture Not available.

**Full text of any H-statements** not written out in full under

None.

Sections 2 to 15

**Revision information** 

Product and Company Identification: Product and Company Identification

Composition / Information on Ingredients: Ingredients Physical & Chemical Properties: Multiple Properties Toxicological Information: Toxicological Data

Ecological Information: Ecotoxicity

**GHS:** Classification

**Training information** 

Not available.

Disclaimer

This information is based on our present knowledge on creation date. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid

contractual relationship.

Material name: ARMORTECH 65AL 418B Version #: 04 Revision date: 04-September-2019 Issue date: 14-March-2013